

GIORGIO GRAESAN and Friends	TECHNICAL SHEET LA CASA DEI SOGNI	Code	TDS1050_00
		Revision	00
		Date	18/05/2018

1. DESCRIPTION

LA CASA DEI SOGNI is an acrylic paint that is easy and intuitive to apply. It is spread with the palm of the hand covered with our PE6 glove. The effect obtained is that of an old wall consumed by time and wear.

2. USE

LA CASA DEI SOGNI can be used on any properly insulated interior surface.

3. PREPARING THE SUBSTRATE

Proper preparation of the substrate is essential for a perfect finish. Therefore, eliminate any peeling or crumbling paint or plaster, taking care to wash or brush any mould or dust. Before applying PRIMUS SABBIA, the surface must always be properly cohesive, otherwise, proceed with an insulating bonding agent, recommended especially in the case of plasterboard walls.

If applying on tiles, after degreasing the wall with denatured ethanol, smooth out any wide grout lines by carefully grouting with PRIMUS AGGRAPPANTE, let dry, then, using a stainless steel KIT/I trowel, apply a coat of PRIMUS AGRAPPANTE, smoothly and evenly.

If a completely smooth surface is desired, once the substrate is dry, we recommend applying a suitable self-levelling putty and an insulating bonding agent.

Next, apply PRIMUS SABBIA.

4. METHOD OF APPLICATION

LA CASA DEI SOGNI is ready for use. Colour by pouring the COLOURING ADDITIVE, previously mixed, in the quantity indicated in the catalogue and mix until the colour is completely homogeneous, taking care not to leave uncoloured product on the bottom or on the sides of the tin.

Wet generously our fur glove with the product. Start distributing the product over the entire wall with an unorganized movement of the palm of your hand. Keep the tip of the glove "unloaded" in the corners. If you want to "age" your work, go over it lightly with a damp glove after 15-30 minutes, creating the original antique stains. If you want greater uniformity, go over it again with the same product.

5. CLEANING THE TOOLS

Clean **LA CASA DEI SOGNI** off tools by rinsing with water.

6. CLEANING THE FINISHED PRODUCT

After 48 hours **LA CASA DEI SOGNI** can be further protected by applying pure VETRO OPACO, VETRO LUCIDO, VETRO SATINATO or IPERVETRO (see the relevant technical sheets).

LA CASA DEI SOGNI can be washed, using LATTE DETERGENTE (diluted 50 ml in 1 liter of water).

7. SAFETY RECOMMENDATIONS AND RISK IDENTIFICATION

The product does not require labelling according to current regulations. Use and store according to current health and safety regulations; after use, do not dispose of containers to the environment; let residue dry thoroughly and handle as special waste. Keep out of the reach of children. If swallowed, seek medical advice immediately and show this container or label. Do not empty into drains, waterways or soil.

For more information, see safety data sheet available on: www.giorgiograesan.it

GIORGIO GRAESAN and Friends	TECHNICAL SHEET LA CASA DEI SOGNI	Code	TDS1050_00
		Revision	00
		Date	18/05/2018

TECHNICAL CHARACTERISTICS: APPLICATION	
Dilution	Product is ready for use
Mixing	Always mix before use
Colouring	169 colours in the catalogue (before use, eliminate any skin and mix)
Tools	Glove PE 6
Primer	PRIMUS SABBIA (at least one hand)
Conditions of application	From +10°C to +30°C with relative humidity < 85%
Number of coats	1
Drying time	Each coat dries in 6 – 8 hours at 20°C
Curing time	24 - 36 hours at 20°C
Protecting	VETRO OPACO, VETRO LUCIDO, VETRO SATINATO or IPERVETRO
Washability	Good washability. Fully washable with LATTE DETERGENTE

TECHNICAL CHARACTERISTICS: COVERAGE	
PRIMUS SABBIA	6 – 7 sqm/litre
LA CASA DEI SOGNI	8 – 9 sqm/litre
VETRO	7 – 8 sqm/litre
IPERVETRO	4 – 6 sqm/litre

TECHNICAL CHARACTERISTICS: COLOURING				
COLOUR	LT. 15	LT. 5	LT. 2,5	LT. 1
C1	558 ml	186 ml	93 ml	37.2 ml
C2	186 ml	62 ml	31 ml	12.4 ml
C3	62 ml	20 ml	10 ml	4 ml
C4	20 ml	7 ml	3.5 ml	1.4 ml

TECHNICAL CHARACTERISTICS: PRODUCT	
Composition	Water, breathable polymers
Specific weight	1.00 ± 0.05 kg/litre
pH	6.2 – 7.5
EU limit value (Directive 2004/42/EC) Cat. A/I: decorative effect coatings (water-borne): 200 g/l	Maximum VOC content 15.00 g/l
Storage conditions	Keep in tightly sealed container, even after use and after cleaning the sides and lid of the tin, in a cool, dry place at temperatures between +5°C and +30°C
Packaging	1 – 2.5 – 5 – 15 liters

Giorgio Graesan & Friends guarantees that the information in this sheet is provided to the best of its experience and its technical and scientific knowledge, however cannot assume any responsibility for the results obtained with their use as the conditions of application are beyond its control. We recommend always checking the actual suitability of the product for each specific case. This sheet nullifies and replaces any previous version.

For more information, call phone number **(+39) 02.9903951** or on **Whatsapp: (+39) 3371410335**.